



**WIRE DIAGRAM**

P1	P2
1	1 (VBUS)
2	2 (DATA -)
3	3 (DATA +)
4	4 (GND)
5	5 (SSRX-)
6	6 (SSRX+)
7	7 (GND_DRIN)
8	8 (SSTX-)
9	9 (SSTX+)
10	10 (SHELL)

**Technical Data**

Voltage Rating	: 30 V/AC max.
Current Rating	: 1Amp max.
Contact Resistance	: 2.00Ohm max
Insulate Resistance	: 10M Ohm/300 VDC / 0.01S
Withstand Voltage	: 100V/AC
Operating Temperature	: -20°C ~ 85°C
Storage Temperature	: 0°C ~ 80°C
Operating Humidity	: 5 ~ 85%RH
Storage Humidity	: 10~90%RH



Computace Electronic Company Limited  
 Info@computace.com  
 www.computace.com

**GENERAL TOLERANCE**  
 X.X ±0.25  
 X.XX ±0.15  
 X.XXX ±0.05  
**ANGLE TOLERANCE ±1°**  
 RADIUS ±0.25  
 HOLE ±0.13

DRAWN	<i>WU JIN YUAN</i>
CHECKED	<i>Fiona</i>
APPROVED	<i>JANE QIN</i>

DATE	2018-06-12	UNIT	mm
DATE	2018-06-12	SIZE	A4
DATE	2018-06-12	SCALE	

PART NUMBER	515-4-8160
PRODUCT TITLE	USB 3.0 Terminal Adaptor
DRAWING NUMBER	
REV.	A1