




Terminal Blocks


Computace Electronic Co., Ltd.
www.computace.com



www.computace.com

Computace Electronic Company Limited has modern, high-precision production and manufacturing equipment and provides one-stop services, including high-speed stamping, precision plastic injection molding, vertical overmolding injection, automatic plug-in assembly, robotic automated soldering, quality inspection, and customized labeling. Additionally, we have established close partnerships with various professional component manufacturers and leading brand distributors worldwide, enabling us to utilize key resources in research, development, and production to manufacture, market, and distribute our products globally. Moreover, various cooperation models, such as OBM/OEM/ODM, can also be used to provide customers with suitable service solutions and professional support.





PLUGGABLE TERMINAL BLOCKS

Page 4-19



SCREWLESS TERMINAL BLOCKS

Page 20-23



PCB TERMINAL BLOCKS

Page 24-36



EUROSTYLE TERMINAL BLOCKS

Page 37-39




BARRIER TERMINAL BLOCKS



Page 40-41

PLUGGABLE TERMINAL BLOCKS

15ESGK



N=No. of Poles
P=Pitch




Unit = mm


SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66,UL94V0 M2,Steel Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated

15ESGKM



N=No. of Poles
P=Pitch




Unit = mm



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2P - 20P
MATERIAL	
Housing screw	PA66,UL94V-0 M2 Steel Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated

15ESGKA



N=No. of Poles
P=Pitch



2P to 6P with wedge,
above 7P without wedge
(Including 7P)


Unit = mm

SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66,UL94V-0 M2 Steel Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated




PLUGGABLE TERMINAL BLOCKS

15ESGKAM



N=No. of Poles
P=Pitch

Unit = mm



2P to 6P with wedge, above
7P without wedge
(Including 7P)

SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-30°C - 120°C
Stripping length	7mm





DIMENSIONS

Wire range	28-16AWG
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 24P

MATERIAL

Housing screw	PBT, UL94V-O M2 Steel Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated

15ESGKB



2P to 6P with wedge,
above 7P without
wedge
(Including 7P)

SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-30°C - 120°C
Stripping length	7mm





DIMENSIONS

Wire range	28-16AWG
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 20P

MATERIAL

Housing screw	PBT, UL94V-O M2 Steel Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated

15ESGKBM



2P to 6P with wedge, above 7P
without wedge
(Including 7P)

SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-30°C - 120°C
Stripping length	7mm

DIMENSIONS


Wire range	28-16AWG
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 24P

MATERIAL

Housing screw	PBT, UL94V-O M2 Steel Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated


PLUGGABLE TERMINAL BLOCKS

15ESGVC



N=No. of Poles
P=Pitch



Unit = mm



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 105°C
DIMENSIONS	
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated



15ESGVM



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 120°C
DIMENSIONS	
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-0
Nut	M2.5 Brass
Contact Cage	Brass, Tin Plated

15ESGRC




SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 105°C
DIMENSIONS	
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated


PLUGGABLE TERMINAL BLOCKS

15ESGRM



N=No. of Poles
P=Pitch

Unit = mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS


Pitch	3.5 mm(. 138"), 3.81mm(. 150")
-------	-----------------------------------

Poles	2P - 24P
-------	----------

MATERIAL

Housing screw	PA66, UL94V-0
Nut	M 2.5 Brass
Contact Cage	Brass, Tin Plated

15ESGVH



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS



Pitch	3.5 mm(. 138"), 3.81mm(. 150")
-------	-----------------------------------

Poles	2P - 24P
-------	----------

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated

15ESGVHM



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS

Pitch	3.5 mm(. 138"), 3.81mm(. 150")
-------	-----------------------------------

Poles	2P - 24P
-------	----------

MATERIAL


Housing screw	PA66, UL94V-0
Nut	M2.5 Brass
Contact Cage	Brass, Tin Plated

PLUGGABLE TERMINAL BLOCKS

15ESGRH





N=No. of Poles
P=Pitch



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 105°C
DIMENSIONS	
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2*2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated



15ESGRHM



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 105°C
DIMENSIONS	
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2*2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-0
Nut	M2.5 Brass
Contact Cage	Brass, Tin Plated

15ESGKC




SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	8A
MECHANICAL	
Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	9mm
DIMENSIONS	
Wire range	28-16AWG
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66,UL94V-0M2,Steel cr+ zn Plated
Contact Cage	Phosphor Bronze Steel, Zn Plated


PLUGGABLE TERMINAL BLOCKS

15ESGKCM



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Striping length	9mm



DIMENSIONS

Wire range	28-16AWG
Pitch	3.81mm(. 150")
Poles	2P - 20P

MATERIAL

Housing screw	PBT,UL94V-O M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Steel Cr ³⁺ Zn Plated

15ESGKD



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	9mm



DIMENSIONS

Wire range	28-16AWG
Pitch	3.81mm(. 150")
Poles	2P - 24P

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Phosphor Bronze Steel, Zn Plated

15ESGKDM



SPECIFICATIONS

t

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	9mm

DIMENSIONS


Wire range	28-16AWG
Pitch	3.5 mm(. 138"), 3.81mm(. 150")
Poles	2P - 20P

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Phosphor Bronze


PLUGGABLE TERMINAL BLOCKS

HTSG396K



N=No. of Poles
P=Pitch



Unit: mm



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	150V
Rated Current	8A
MECHANICAL	
Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-14AWG
Pitch	3.96mm(0.156")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-O M2 Steel Ni Plated
Contact Cage	Brass Tin Plated
Wire guard	Phosphor Bronze



HTSG396V



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	150V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 105°C
DIMENSIONS	
Pitch	3.96mm(0.156")
Poles	2P-24P
MATERIAL	
Housing screw	PA66, UL94V-O
Contact Cage	Brass, Tin Plated

HTSG396R



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	150V
Rated Current	8A
MECHANICAL	
Operating Temp	-40°C - 105°C
DIMENSIONS	
Wire range	28-16AWG
Pitch	3.96mm(0.156")
Poles	2P - 24P
MATERIAL	
Housing screw	PA66, UL94V-O
Contact Cage	Brass Tin Plated



PLUGGABLE TERMINAL BLOCKS

SG332K



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-30°C - 120°C
Stripping length	5-6mm



DIMENSIONS

Wire range	28-16AWG
Pitch	5.0mm(0.197")
Poles	2P,3P - 24P

MATERIAL

Housing screw	PBT,UL94V-O M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated
Contact Cage	Phosphor Bronze, Brass, Ni Plated

SG332J



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------




DIMENSIONS

Pitch	5.0mm(0.197")
Poles	2P,3P - 24P

MATERIAL

Housing screw	PA66+10%GF, UL94V-O
Contact Cage	Brass, Tin Plated

15ESGKB



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm

DIMENSIONS


Wire range	28-16AWG
Pitch	3.5mm(0.138")
Poles	2P - 20P

MATERIAL

Housing screw	PBT,UL94V-O M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass, Ni Plated



PLUGGABLE TERMINAL BLOCKS

2ESGK



N=No. of Pins
P=Pitch




Unit: mm



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	15A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P-24P / 2P-12P
MATERIAL	
Housing screw	PA66, UL94V-O M3Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass, Ni Plated





2ESGKM



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	15A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P-24P / 2P-12P
MATERIAL	
Housing screw	PA66, UL94V-O M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass, Ni Plated

2ESGKA




SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	15A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P-24P / 2P-12P
MATERIAL	
Housing screw	PA66, UL94V-O M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass, Ni Plated


PLUGGABLE TERMINAL BLOCKS

2ESGKAM



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm



DIMENSIONS

Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P-24P / 2P-12P

MATERIAL

Housing screw	PA66, UL94V-O M3Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass, Ni Plated

2ESGKB



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm



DIMENSIONS

Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P-24P / 2P-12P

MATERIAL

Housing screw	PA66, UL94V-O M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass, Ni Plated

2ESGKBM



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm

DIMENSIONS


Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P-22P / 2P-12P

MATERIAL

Housing screw	PA66, UL94V-O M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass, Ni Plated


PLUGGABLE TERMINAL BLOCKS

2ESGV



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS



Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
-------	--

Poles	2P-24P / 2P-12P
-------	-----------------

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Brass, Ni Plated

2ESGR



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS



Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
-------	--

Poles	2P-24P / 2P-12P
-------	-----------------

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Brass, Ni Plated

2ESGVC



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

Stripping length	7mm
------------------	-----

DIMENSIONS

Wire range	28-12AWG
------------	----------

Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
-------	--


Poles	2P-24P / 2P-12P
-------	-----------------

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Brass, Ni Plated





PLUGGABLE TERMINAL BLOCKS

2ESGVM



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS






Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
-------	--

Poles	2P-24P / 2P-12P
-------	-----------------

MATERIAL

Housing screw	PA66, UL94V-0
Nut	M2.5 Brass
Contact Cage	Brass, Ni Plated

2ESGRC



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

Stripping length	7mm
------------------	-----

DIMENSIONS






Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
-------	--

Poles	2P-24P / 2P-12P
-------	-----------------

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Ni Plated

2ESGRM



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

Stripping length	7mm
------------------	-----

DIMENSIONS

Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
-------	--


Poles	2P-24P / 2P-12P
-------	-----------------

MATERIAL

Housing screw	PA66, UL94V-0
Nut	M2.5 Brass
Contact Cage	Brass, Ni Plated


PLUGGABLE TERMINAL BLOCKS

2ESGVH



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------



DIMENSIONS

Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2*(2P - 24P)

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Brass, Tin Plated

2ESGRH



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------



DIMENSIONS

Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2*(2P - 24P)

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Brass, Tin Plated

2ESGVHM



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS


Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2*(2P - 24P)

MATERIAL

Housing screw	PA66, UL94V-O
Nut	M2.5 Brass
Contact Cage	Brass, Tin Plated





PLUGGABLE TERMINAL BLOCKS

2ESGRHM



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS






Pitch	5.0mm(0.197") 5.08mm(0.200")
-------	---------------------------------

Poles	2*(2P - 24P)
-------	--------------

MATERIAL

Housing screw	PA66, UL94V-0
Nut	M2.5 Brass
Contact Cage	Brass, Tin Plated

2ESGKC



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C

Stripping length	10mm
------------------	------






DIMENSIONS

Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P-24P 2P-12P

MATERIAL

Housing screw	PA66, UL94V-0 M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Steel

2ESGKCM



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C

Stripping length	10mm
------------------	------

DIMENSIONS


Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P-24P 2P-12P

MATERIAL

Housing screw	PA66, UL94V-0 M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Steel



PLUGGABLE TERMINAL BLOCKS

2ESGKL



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm




DIMENSIONS

Wire range	24-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P-24P

MATERIAL

Housing screw	PA66, UL94V-O M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated

2ESGKLM



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm




DIMENSIONS

Wire range	24-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P - 22P

MATERIAL

Housing screw	PA66, UL94V-O M2.5Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated

2ESGKD



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	10mm

DIMENSIONS


Wire range	26-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P - 16P 2P - 12P

MATERIAL

Housing screw	PA66, UL94V-O
Contact Cage	Phosphor Bronze Brass, Ni Plated




PLUGGABLE TERMINAL BLOCKS

2ESGKDM



N=No. of poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	10mm




DIMENSIONS

Wire range	26-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P- 16P 2P - 12P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Phosphor Bronze Steel

2CSGB



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Operating Temp	-40°C - 105°C
----------------	---------------

DIMENSIONS


Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P- 16P 2P - 12P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass Tin Plated


SCREWLESS TERMINAL BLOCKS

SG141V



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	150V
Rated Current	2A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	11mm



DIMENSIONS

Wire range	24-20AWG
Pitch	2.54mm(0.100")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel

SG141R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	150V
Rated Current	2A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	11mm



DIMENSIONS

Wire range	24-20AWG
Pitch	2.54mm(0.100")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel

SG142V



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	10mm

DIMENSIONS

Wire range	22-16AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")


Poles	2P- 24P
-------	---------

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel



SCREWLESS TERMINAL BLOCKS

SG142R



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	10mm




DIMENSIONS

Wire range	22-14AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel

SG142V



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	10mm




DIMENSIONS

Wire range	22-16AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel

SG211R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	*A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	8-9mm

DIMENSIONS

Wire range	22-16AWG
Pitch	3.5mm(0.138") 5.00mm(0.197")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel


SCREWLESS TERMINAL BLOCKS

SG211V



N=No. of Pins
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	8A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	8-9mm



DIMENSIONS

Wire range	22-16AWG
Pitch	3.5mm(0.138") 5.00mm(0.197")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass, Tin Plated Steel

SG250



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	2A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	8.5-9.5mm



DIMENSIONS

Wire range	24-20AWG
Pitch	2.5mm(0.98") 2.54mm(0.100")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Phosphor Bronze Steel

SG250L



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	7A

MECHANICAL

Operating Temp	-40°C - 105°C
Striping length	8.5-9.5mm

DIMENSIONS

Wire range	22-18AWG
Pitch	3.5mm(0.138") 7.00mm(0.276")
Poles	2P- 24P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Phosphor Bronze Steel




SCREWLESS TERMINAL BLOCKS

SG235



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	5A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	9-10mm


DIMENSIONS

Wire range	22-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P- 24P




MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Phosphor Bronze Tin Plated

SG295



No. of Poles	A	B	C	D
3	9.14	18.14	N/A	14.13
4	13.71	22.11	N/A	18.29
5	18.28	27.28	2.79	18.29
6	22.85	31.85	2.79	18.29
7	27.42	36.42	1.37	18.29
8	31.99	41.01	1.37	18.29
9	36.56	45.57	11.94	18.29
10	41.13	40.14	11.94	18.29



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	2A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	8-9mm






DIMENSIONS

Wire range	24-18AWG
Pitch	4.75mm(0.180")
Poles	3P-10P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Phosphor Bronze Tin Plated

SG237



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Operating Temp	-40°C - 105°C
Stripping length	10mm

DIMENSIONS


Wire range	22-16AWG
Pitch	5.08mm(0.200")
Poles	2P- 7P

MATERIAL

Housing screw	PA66, UL94V-0
Contact Cage	Brass Tin Plated


PCB TERMINAL BLOCKS

SG381



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	150V
Rated Current	10A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5mm


DIMENSIONS

Wire range	26-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2P, 3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated

SG381H



SPECIFICATIONS

ELECTRICAL

Rated Voltage	150V
Rated Current	10A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5mm


DIMENSIONS

Wire range	26-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2P, 3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated

SG381B



SPECIFICATIONS

ELECTRICAL

Rated Voltage	150V
Rated Current	10A

MECHANICAL

Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5mm

DIMENSIONS


Wire range	26-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2*(2P,3P-25P)

MATERIAL

Housing screw	PA66, UL94V-O, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated


PCB TERMINAL BLOCKS

SG381A



N=No. of PEs
P=Pitch



Unit: mm



SPECIFICATIONS


ELECTRICAL	
Rated Voltage	150V
Rated Current	10A
MECHANICAL	
Torque	0.2Nm (1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5mm
DIMENSIONS	
Wire range	26-16AWG
Pitch	3.5 mm(0.138"), 3.81mm(0.150")
Poles	2*(2P,3P-24P)
MATERIAL	
Housing screw	PA66, UL94V-O, M2 Steel, Cr3+ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated

SG330



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	150V
Rated Current	15A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-30°C - 105°C
Striping length	7mm
DIMENSIONS	
Wire range	22-12AWG
Pitch	5.0mm(0.197")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated, Brass Ni Plated






SG103

SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	10A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Striping length	7mm
DIMENSIONS	
Wire range	24-12AWG
Pitch	5.0mm(0.197")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated, Brass Ni Plated

PCB TERMINAL BLOCKS






SG103L



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	10A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	24-12AWG
Pitch	5.00mm (0.197") 7.50mm (0.295")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-0, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated





SG500



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	10A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	24-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated

SG500H




SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	20A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	28-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Phosphor Bronze Brass Ni Plated


PCB TERMINAL BLOCKS

SG500B



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm


DIMENSIONS

Wire range	24-12AWG
Pitch	5.00mm (0.197") 5.08mm(0.200")
Poles	2*(2P,3P-24P)

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG500A



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm



DIMENSIONS

Wire range	24-12AWG
Pitch	5.00mm (0.197") 5.08mm(0.200")
Poles	2*(2P,3P-24P)

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG128



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm

DIMENSIONS


Wire range	24-12AWG
Pitch	5.00mm (0.197") 7.50mm(0.295")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated



PCB TERMINAL BLOCKS

SG125



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm



DIMENSIONS

Wire range	24-12AWG
Pitch	5.00mm (0.197")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG125R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm



DIMENSIONS

Wire range	24-12AWG
Pitch	5.00mm (0.197")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG129



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	20A

MECHANICAL

Torque	0.5Nm(4.4Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm

DIMENSIONS


Wire range	26-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M3 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated


PCB TERMINAL BLOCKS

SG129R



N=No. of Pins
P=Pitch



Unit: mm



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	20A
MECHANICAL	
Torque	0.5Nm(4.4Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	26-12AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M3 Steel, Cr3+ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated



SG127



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	12A
MECHANICAL	
Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6mm
DIMENSIONS	
Wire range	26-14AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M2.5 Steel, Cr3+ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG130




SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	20A
MECHANICAL	
Torque	0.5Nm(4.4Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm
DIMENSIONS	
Wire range	26-14AWG
Pitch	5.0mm(0.197") 5.08mm(0.200") 7.5mm(0.295") 7.62mm(0.300")
Poles	2P,3P-24P
MATERIAL	
Housing screw	PA66, UL94V-O, M3 Steel, Cr3+ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated


PCB TERMINAL BLOCKS

SG128RO



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	7mm



DIMENSIONS

Wire range	24-12AWG
Pitch	5.00mm (0.197")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG127A



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	12A

MECHANICAL

Torque	0.4Nm(3.5Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6mm



DIMENSIONS

Wire range	26-14AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2*(2P,3P-24P)

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Brass Ni Plated

SG636



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	30A

MECHANICAL

Torque	0.5Nm(4.4Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	8mm

DIMENSIONS

Wire range	26-10AWG
Pitch	6.35mm(0.250") 7.62mm(0.300") 9.52mm(0.374")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M3 Steel, Cr ³⁺ Zn Plated
Contact Cage	Copper, Tin Plated Brass Ni Plated


PCB TERMINAL BLOCKS

SG950



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	30A

MECHANICAL

Torque	
Operating Temp	-40°C - 105°C
Striping length	8-9mm



DIMENSIONS

Wire range	26-12AWG
Pitch	9.52mm(0.374")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M3 Steel, Cr3+ Zn Plated
Contact Cage	Copper Tin Plate Brass Ni Plated

SG136



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	50A

MECHANICAL

Torque	
Operating Temp	-40°C - 105°C
Striping length	10mm


DIMENSIONS

Wire range	20-6AWG
Pitch	10.16mm(0.400")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M4 Steel, Cr3+ Zn Plated
Contact Cage	Copper Tin Plate Brass Ni Plated

SG636C



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	30A

MECHANICAL

Torque	0.5Nm(4.4Lb-In.)
Operating Temp	-40°C - 105°C
Striping length	8mm

DIMENSIONS


Wire range	26-10AWG
Pitch	6.35mm(0.250") 9.52mm(0.374")
Poles	2*(2P,3P-24P)

MATERIAL

Housing screw	PA66, UL94V-O, M3 Steel, Cr3+ Zn Plated
Contact Cage	Copper Tin Plate Brass Ni Plated


PCB TERMINAL BLOCKS

SG340



N=No. of Pins
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	30A

MECHANICAL

Torque	0.2Nm(1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5-6mm



DIMENSIONS

Wire range	24-18AWG
Pitch	3.5mm(0.138") 3.81mm(0.150")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG340R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	7A

MECHANICAL

Torque	0.2Nm(1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5-6mm



DIMENSIONS

Wire range	24-18AWG
Pitch	3.5mm(0.138") 3.81mm(0.150")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG350



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	7A

MECHANICAL

Torque	0.2Nm(1.7Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	5-6mm

DIMENSIONS


Wire range	24-18AWG
Pitch	3.5mm(0.138") 3.81mm(0.150")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze


PCB TERMINAL BLOCKS

SG350R



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	7A

MECHANICAL

Torque	0.2Nm(1.7Lb-In.)
Operating Temp	-40°C - 105°C
Striping length	5-6mm


DIMENSIONS

Wire range	24-18AWG
Pitch	3.5mm(0.138") 3.96mm(0.156")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG301



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.2Nm(1.7Lb-In.)
Operating Temp	-40°C - 105°C
Striping length	5-6mm



DIMENSIONS

Wire range	22-14AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG301R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.2Nm(1.7Lb-In.)
Operating Temp	-40°C - 105°C
Striping length	5-6mm

DIMENSIONS


Wire range	22-14AWG
Pitch	5.0mm(0.197") 5.08mm(0.200")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O, M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze


PCB TERMINAL BLOCKS

SG300



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.5Nm(4.4 Lb-In.)
Operating Temp	-30°C - 120°C
Stripping length	5-6mm



DIMENSIONS

Wire range	22-14AWG
Pitch	5.0mm(0.197") 7.5mm(0.295")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M3 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG300R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.5Nm(4.4 Lb-In.)
Operating Temp	-30°C - 120°C
Stripping length	5-6mm



DIMENSIONS

Wire range	22-14AWG
Pitch	5.0mm(0.197") 7.5mm(0.295")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M3 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG166



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.5Nm(4.4 Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6-7mm

DIMENSIONS


Wire range	22-12AWG
Pitch	5.0mm(0.197")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M3 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze


PCB TERMINAL BLOCKS

SG167



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.4Nm(3.5 Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6-7mm


DIMENSIONS

Wire range	22-12AWG
Pitch	5.0mm(0.197") 7.62mm(0.300")
Poles	2P-12P

MATERIAL

Housing screw	PA66, UL94V-O M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG167R



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.4Nm(3.5 Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6-7mm



DIMENSIONS

Wire range	22-12AWG
Pitch	5.0mm(0.197") 7.62mm(0.300")
Poles	2P-12P

MATERIAL

Housing screw	PA66, UL94V-O M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

SG126



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5 Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6-7mm

DIMENSIONS


Wire range	26-14AWG
Pitch	5.0mm(0.197")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M2.5 Steel, Cr ³⁺ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze





PCB TERMINAL BLOCKS

SG126R



N=No. of Pins
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	10A

MECHANICAL

Torque	0.4Nm(3.5 Lb-In.)
Operating Temp	-40°C - 105°C
Stripping length	6-7mm

DIMENSIONS


Wire range	22-14AWG
Pitch	5.0mm(0.197") 7.5mm(0.295")
Poles	2P,3P-24P

MATERIAL

Housing screw	PA66, UL94V-O M2.5 Steel, Cr3+ Zn Plated
Contact Cage	Brass Tin Plated Phosphor Bronze

TERMINAL BLOCKS COLLECTION


PLUGGABLE TERMINAL BLOCKS



BARRIER TERMINAL BLOCKS



SCREWLESS TERMINAL BLOCKS




EUROSTYLE TERMINAL BLOCKS






EUROSTYLE TERMINAL BLOCKS

SGPA8F



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	20A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------





DIMENSIONS

Wire range	12-22AWG
Pitch	8.2mm(0.323")
Poles	2P - 12P

MATERIAL

Housing screw	PA66, UL94V-2 M2.6 x 5 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated

SGPA10F



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	30A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------




DIMENSIONS

Wire range	10-22AWG
Pitch	10.0mm(0.394")
Poles	2P - 12P

MATERIAL

Housing screw	PA66, UL94V-2 M2.6 x 5 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated

SGPA10H



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	30A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------

DIMENSIONS


Wire range	10-22AWG
Pitch	10.0mm(0.394")
Poles	2P - 12P

MATERIAL

Housing screw	PA66, UL94V-2 M3 x 6 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated


EUROSTYLE TERMINAL BLOCKS

SGPA12H



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	35A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------



DIMENSIONS

Wire range	10-22AWG
Pitch	12.0mm(0.472")
Poles	2P-12P

MATERIAL

Housing screw	PA66, UL94V-2 M3.5x 7 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated

SG15H



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	50A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------



DIMENSIONS

Wire range	12-8AWG
Pitch	15.0mm(0.591")
Poles	2P-12P

MATERIAL

Housing screw	PA66, UL94V-2 M4 x 9 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated

SG10HT-2.0



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	30A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------

DIMENSIONS


Wire range	10-22AWG
Pitch	10.0mm(0.394")
Poles	2P-12P

MATERIAL

Housing screw	PA66, UL94V-2 M3 x 6 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated


EUROSTYLE TERMINAL BLOCKS

SG10HT



N=No. of Poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	600V
Rated Current	30A

MECHANICAL

Operating Temp	-40°C - 110°C
----------------	---------------



DIMENSIONS

Wire range	10-22AWG
Pitch	10.0mm(0.394")
Poles	2P-12P

MATERIAL

Housing screw	PA66, UL94V-2 M3x 6Steel Cr ³⁺ Zn Plated
Contact Cage	Copper strip Cr ³⁺ Zn Plated

SG4T



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	30A

MECHANICAL

Operating Temp	-30°C - 85°C
----------------	--------------




DIMENSIONS

Wire range	10-20AWG
Pitch	14.0mm(0.551")
Poles	2P-10P

MATERIAL

Housing screw	PA66, UL94V-2 M4 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper

SG6T



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	30A

MECHANICAL

Operating Temp	-30°C - 85°C
----------------	--------------

DIMENSIONS

Wire range	8-16AWG
Pitch	16.0mm(0.630")
Poles	2P-10P

MATERIAL

Housing screw	PA66, UL94V-2 M3 Steel Cr ³⁺ Zn Plated
Contact Cage	Copper



BARRIER TERMINAL BLOCKS

SG25C-B



N=No. of poles
P=Pitch

Unit: mm



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.5N.m 4.4Lb.in
Operating Temp	-40°C - 105°C



DIMENSIONS

Wire range	14-22AWG
Pitch	7.62mm(.300")
Poles	2P-26P

MATERIAL

Housing screw	PA66, UL94V-2 M3 Steel Ni Plated
Contact Cage	Brass Tin Plated

SG25S-B



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	15A

MECHANICAL

Torque	0.5N.m 4.4Lb.in
Operating Temp	-40°C - 105°C



DIMENSIONS

Wire range	14-22AWG
Pitch	7.62mm(.300")
Poles	2P-26P

MATERIAL

Housing screw	PA66, UL94V-2 M3 Steel Ni Plated
Contact Cage	Brass Tin Plated

SG65C-B



SPECIFICATIONS

ELECTRICAL

Rated Voltage	300V
Rated Current	20A

MECHANICAL

Torque	1.2N.m 10.6 Lb.in
Operating Temp	-40°C - 105°C

DIMENSIONS

Wire range	12-22AWG
Pitch	11.0mm(0.433")
Poles	2P-22P

MATERIAL

Housing screw	PA66, UL94V-2 M4 Steel Ni Plated
Contact Cage	Brass Tin Plated


BARRIER TERMINAL BLOCKS

SG45C-B



N=No. of Poles
P=Pitch


Unit: mm



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	25A
MECHANICAL	
Torque	1.2N.m 10.6 Lb.in
Operating Temp	-40°C - 105°C
DIMENSIONS	
Wire range	12-22AWG
Pitch	9.5 mm(0.375")
Poles	2P-22P
MATERIAL	
Housing screw	PA66, UL94V-2 M4 Steel Ni Plated
Contact Cage	Brass Tin Plated


SG45R-B



SPECIFICATIONS


ELECTRICAL	
Rated Voltage	300V
Rated Current	25A
MECHANICAL	
Torque	1.2N.m 10.6 Lb.in
Operating Temp	-40°C - 105°C
DIMENSIONS	
Wire range	12-22AWG
Pitch	9.5 mm(0.375")
Poles	2P-22P
MATERIAL	
Housing screw	PA66, UL94V-2 M4 Steel Ni Plated
Contact Cage	Brass Tin Plated

SG48C-B



SPECIFICATIONS

ELECTRICAL	
Rated Voltage	300V
Rated Current	20A
MECHANICAL	
Torque	1.2N.m 10.6 Lb.in
Operating Temp	-40°C - 105°C
DIMENSIONS	
Wire range	12-22AWG
Pitch	9.5 mm(0.375")
Poles	2P-22P
MATERIAL	
Housing screw	PA66, UL94V-2 M4 Steel Ni Plated
Contact Cage	Brass Tin Plated



www.computace.com

COMPUTACE ELECTRONIC COMPANY LIMITED

No.6 Guangkou St., Hengli Town,
Dongguan City, Guangdong, China
info@computace.com